



# BrakeVac II

## Premium Brake Fluid Flush System

### Part No. 500-8100

The BrakeVac II brake bleeder machine is a simple, user friendly and efficient way to flush and bleed today's high tech brake systems. The BrakeVac II reduces the concerns associated with both air pressure and vacuum style brake bleeding. This system can complete a full brake system flush in 10 minutes with only one operator thereby lowering labor costs and maximizing profits.

- Performs brake flush using pressure and vacuum simultaneously.
- Vacuum pump to easily remove fluid from brake fluid reservoir.
- Complete brake system flush in just 10 minutes.
- Pressure and vacuum assist, ensuring quick operation.
- Adjustable pressure regulator controls operating pressure.
- 1 gallon (3.78L) fluid tank & removable waste tank for multiple services.
- Drain switch to empty new fluid tank for changing to different brake fluids.
- Extra long 10 foot pressure hose with quick disconnect coupler assures full lift extension.
- Easy to view tank allows for fast visual check of fluid in the reservoir.



\* BrakeVac II unit may also be purchased without adapters. Part number 500-8105. OEM specific adapters are available.

### PART NO. 200-3118M STANDARD ADAPTERS (INCLUDED)



PART NO.	QTY	DESCRIPTION
066-6000	1	2-piece, 3 Tabs, Expandable O-Rings
066-6002	1	3 Tab Twist On With Expandable O-Ring BA-03
066-6003	1	3 Tab Twist On With Expandable O-Ring BA-04
066-6004	1	Threaded Screw Cap
066-6005	1	Universal Round Adapter With Chain Tension Hold Down
066-6006	1	Expandable O-Ring With Hold Down Chain 2.91" Diameter
066-6007	1	Expandable O-Ring With Hold Down Chain 2.11" - 2.17" Diameter
066-6008	1	Expandable O-Ring With Adjustable Hold Down Tabs 1.69" Diameter
066-6009	1	Expandable O-Ring With Adjustable Hold Down Tabs 2.75" Diameter
066-6010	1	Twin Cylinders With Rubber Cones Connected Together With Common Hose
066-6012	1	Twist On 2 Tab With Expandable O-Ring
066-6013	1	Twist On 2 Tab With Expandable O-Ring - Nissan Altima, Xterra

Specifications			
Power Cord	16.5' (5m)	Shipping Height	41" (104 cm)
Power Supply	12 volt DC	Shipping Width	24" (61 cm)
New Fluid Capacity	1 Gal. (3.79L)	Shipping Depth	19" (48 cm)