## P-9000LT

**BP BendPak** 

Low-Mid Rise Lifts SKU# 5175133 9,000-lb. Capacity / Low-Rise Lift / Open-Center / Pit-Style Questions? Contact BendPak's Sales Team sales@bendpak.com | 1-800-253-2363 Monday - Friday, 6AM to 4:30PM PST

## World-Class Power, Simple Design Pit-Style Low-Rise Lift

The 9,000-lb. capacity P-9000LT is a heavier-duty version of the P-6B. We increased the lift capacity by 30% while maintaining all the features you love: dual-approach design, open-center access and a hands-free safety check. This is the industry's ultimate pit lift, perfect for quick-lube shops, full auto centers and home garages. Minimal footprint and full access to the wheels and undercarriage. Ramps attach and detach quickly to convert a flush-mount unit to a floor unit.



## **Features**

- Easily convert fast-lube pits into wheel service work bays
- Mounts outside the pit rail without interfering with center work area
- Model P-9000LTF flush-mount model provides recessed drive-over option
- Heavy duty 1.5 HP electric-hydraulic power unit
- Electronic push-button controls allow smooth, singlehand operation
- Automatic multi-position safety locks with air release deliver safe, remote operation
- Durable rubber-topped pad surface and rubber lift blocks provide quick set-up

## **Specifications**

<b>Lifting Capacity</b>	9,000 lbs. (4,082 kg)
Platform Length	58.5" (1,484 mm)
Platform Width	24" (610 mm)
Lift Height	23.3" (592 mm)
Lift Height + Blocks	26.3" (668 mm)
Overall Length	124.6" (3,165 mm)
Lowered Height	3.15" (80 mm)
Speed of Rise	55 sec
Standard Motor (*)	1.5 HP / 110-220 VAC / 60 Hz / 1Ph

<sup>\*</sup> Multi-station power unit and special voltages available upon request. The design, material and specifications are subject to change without notice.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.