

HOFMANN®



monty™ 1575

TIRE CHANGER

monty™ 1575



The monty 1575 is ideal for shops looking for great value without sacrificing productivity. It includes wheel protectors so even the most expensive wheels can be changed without additional expense and fear of cosmetic damage. The monty 1575 can also be upgraded by adding Hofmann's patented EasyMont Pro, aiding in single-operator mounting/demounting of extra-stiff, low-profile, high-performance and run-flat tires.

Accommodates Large Wheel & Tire Assemblies

Allowing for a tire diameter of 40", and outer-wheel diameters of 21", the monty 1575 can handle wheel and tire assemblies found on cars and light trucks.

Dual Wheel Clamping Cylinders

Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage.

Adjustable Four-Jaw Clamping Chuck

Self-centering and clamps wheels with either 26" inner or 24" outer diameter.

Powerful Two-Stage Bead Breaker

6,000 lbs. of power at the bead shovel and a range of up to 14" wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads!

Powerful Tire Inflation System

Powerful air blast operated by the foot pedal. Each moveable jaw is precisely set to the exact position under the wheel to seal the tire bead.

Upgrade With Optional EasyMont Pro!

EasyMont Pro features a three-piece design with a Top Roller, Pressing Foot, and Lifting Disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires.

SPECIFICATIONS

	monty1575
Overall Wheel Clamping Diameter	10" - 26"
Inner-Wheel Clamping Diameter	12" - 26"
Outer-Wheel Clamping Diameter	10" - 24"
Bead Breaker Range:	3" - 13"
Bead Loosening Power:	6,000 lbs.
Maximum Wheel Width:	13"
Maximum Outer Tire Diameter:	39"
Shipping Weight:	550 lbs.
Drive Motor Electric Option:	1HP
Power Requirements*	120V, 1Ph, 60Hz

* Other Power Configurations Available

OPTIONAL ACCESSORIES

EasyMont Pro bead assist device	EAA0329G35B
Automotive adapters: (28" outer clamping diameter)	EAA0332G91A
Motorcycle adapters: (12" - 23" outer clamping diameter)	EAA0329G53A
ATV adapters (4 each): (6" - 17" outer clamping diameter)	EAA0332G84A
Quick change bead head kit:	4028228
Composite mount/demount head:	EAA0247G20A
Protective cover (for tire lever):	EAA0247G04A
Outside clamping jaw protectors (4 each):	EAA0304G20A
Snap-in jaw protector:	ST0022129
Protective cover for bead breaker shovel:	EAA0304G15A
Rim protector, snaps onto rim of wheel: (3 each - use with wave tire tool)	ST4026853
Protective insert for mount/demount head (10 EA):	EAA0247G15A
Replacement composite head:	ST0024335
Wave tire tool:	EAA0304G14A
Magic bead pusher (use with EasyMont):	ST4028648
Round bar with roller attachment (35mm): (Use with EasyMont)	EAA0332G32A
Hex bar with roller attachment: (Use with EasyMont)	EAA0329G92A
Bead breaker disc (Use with hex bar):	EAA0304G43A
Bead clamp for performance wheels:	EAA0247G70A
Bead clamp for run-flat tires:	EAA0247G11A
Premium tire paste	RTT75NKIT



USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca