

Call: 1-800-445-8244 Visit: AutoBodyShop.Com

Made in the USA



Strong, portable removable ramps.

Specifications

Length of bed: (top) 20 ft. (610 cm) Length w/towers extended: 24 ft. 3 in. (739 cm) (5 tower machine) Width of bed: 88 in. (224 cm) Width w/towers extended: 14 ft. 4 in. (437 cm) Width of treadway: 28 in. (71 cm) Weight: 5 tower 8,100 lbs (3674 kg), 4 tower 7,650 lbs (3470 kg), 3 tower 7,050 lbs (3198 kg) Width between treadways: 32 in. (81 cm) Overall height: 9 ft. 3 in. (282 cm) Working height: 31 in. (79 cm) Hydraulics: 10 & 5 ton (9 & 4.5 metric ton)(5 tower machine) Power required: 120v, 20 amp dedicated service. Optional tower configurations: 3, 4 or 5 towers Lift capacity: 10,000 lbs. (4536 kg)

Specifications are subject to change without notice.



One control for hydraulic pump operation. Each tower has it's own hydraulic gauge and valve control.



Three towers pivot from the large drum which also stores the electric over hydraulic pump.

Sign 9013 9013 9013

Combination Package 9020029

Ask about our other popular optional tools.





Signature 9013301 – 3 tower 9013401 – 4 tower 9013501 – 5 tower

Signature"

Call: 1-800-445-8244 Visit: AutoBodyShop.Com