

*Signature*  
**HYBRID**



Choose between  
20 ft. (610 cm) or  
22 ft. (671 cm)  
models



**Two Tower Styles,  
One Machine.**



**Signature  
Hybrid**

**USA Made  
Frame Machine**

**Call: 1-800-445-8244  
Visit: [AutoBodyShop.Com](http://AutoBodyShop.Com)**

**Made  
in the USA**



Bed mounted hydraulic quick connectors.



Roller bearing tower.

## Specifications

- Length of bed: (top) 20 ft. (610 cm)
- Length w/towers extended: 24 ft. 6 in. (747 cm)
- Width of bed: 88 in. (224 cm)
- Width w/towers extended:
- Pivot end 13 ft. 4 in. (406 cm), Track end 11 ft. 4 in. (345 cm)
- Width of treadway: 28 in. (71 cm)
- Width between treadways: 32 in. (81 cm)
- Overall height: 9 ft. 3 in. (282 cm)
- Working height: 31 in. (79 cm)
- Hydraulics: 10 ton (9 metric tons)
- Power required: 120v, 20 amp dedicated service.
- Lift capacity: 12,000 lbs. (5443 kg)

Specifications are subject to change without notice.  
 Specifications above are for 20 ft. (610 cm) model



Universal style anchoring/clamping.

### Signature Hybrid

20' (610 cm)

9012800 - 2-1 tower

9012801 - 3-1 tower

9012802 - 3-2 tower

### Signature Hybrid

22' (671 cm)

9012810 - 2-1 tower

9012811 - 3-1 tower

9012812 - 3-2 tower



Combination Package 9020029

Ask about our other popular optional tools.

Choose between 20 ft. (610 cm) or 22 ft. (671 cm) models.

Also choose between the available combinations of main pivoting and roller bearing towers.



Roller bearing tower

**Call: 1-800-445-8244**  
**Visit: AutoBodyShop.Com**